NN-45B-HG-R1B

4-port Next Generation PerforMax™ Superior Coverage and Capacity sector antenna, 4x 698–896 MHz, 45° HPBW, 6 ft, 1x RET

- Superior patterns for enhanced interference mitigation resulting in improved SINR, higher throughput, and more capacity
- Best in class PIM immunity
- Antenna optimized for higher gain with superior radiation efficiency
- Powered by Andrew's SEED® technology (Sustainable Energy Efficient Design)
- Internal SBTs allow remote RET control from the radio over the RF jumper cable
- Ideal 4T4R low band antenna for use with an FD mMIMO antenna

General Specifications

Antenna Type	Sector
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Radiator Material	Aluminum | Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, low band	4
RF Connector Quantity, total	4

Remote Electrical Tilt (RET) Information

RET Hardware	CommRET v2
RET Interface	8-pin DIN Female | 8-pin DIN Male
RET Interface, quantity	1 female | 1 male
Input Voltage	10–30 Vdc
Internal Bias Tee	Port 1
Internal RET	Low band (1)
Power Consumption, active state, maximum	10 W

©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: May 28, 2026

NN-45B-HG-R1B

Power Consumption, idle state, maximum	2 W
Protocol	3GPP/AISG 2.0 (Single RET)

Dimensions

Width	749 mm | 29.488 in
Depth	197 mm | 7.756 in
Length	1848 mm | 72.756 in
Net Weight, without mounting kit	48 kg | 105.822 lb

Array Layout



Array ID	Frequency (MHz)	RF Connector	RET	AISG No.	SBT	SBT No.	RET UID
R1	698-896	1 - 2	1	AISG1	1	1	ANxxxxxxxxxxxxxxR1
R2	698-896	3 - 4					

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration

©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: May 28, 2026

NN-45B-HG-R1B

Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	698 – 896 MHz
Polarization	±45°
Total Input Power, maximum	600 W @ 50 °C

Electrical Specifications

	R1,R2	**R1,R2**
Frequency Band, MHz	**698–806**	**806–896**
RF Port	1-4	1-4
Gain, Maximum, dBi	17	17.5
Gain, dBi	16.5	17.1
Beamwidth, Horizontal, degrees	48	44
Beamwidth, Vertical, degrees	11.4	9.8
Beam Tilt, degrees	2–12	2–12
USLS (First Lobe), dB	16	15

©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: May 28, 2026

NN-45B-HG-R1B

Front-to-Back Ratio at 180°, dB	26	31
Front-to-Back Ratio, Copolarization 180° ± 30°, dB	25	29
CPR at Boresight, dB	17	19
Isolation, Cross Polarization, dB	25	25
Isolation, Inter-band, dB	25	25
VSWR | Return loss, dB	1.5 | 14.0	1.5 | 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153
Input Power per Port at 50°C, maximum, watts	300	300

Mechanical Specifications

Wind Loading @ Velocity, frontal	1,768.0 N @ 150 km/h (397.5 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	191.0 N @ 150 km/h (42.9 lbf @ 150 km/h)
Wind Loading @ Velocity, maximum	1,768.0 N @ 150 km/h (397.5 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	1,768.0 N @ 150 km/h (397.5 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	910 mm | 35.827 in
Depth, packed	356 mm | 14.016 in
Length, packed	2438 mm | 95.984 in
Weight, gross	74.5 kg | 164.244 lb

Regulatory Compliance/Certifications

Agency	**Classification**
UK-ROHS	Compliant

Included Products

BSAMNT-9	–	Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

* Footnotes

Performance Note	Severe environmental conditions may degrade optimum performance

©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: May 28, 2026