1.0 GENERAL NOTES REVISIONS 1.1 ALL METRIC DIMENSIONS ARE IN BRACKETS [X. X] APPROVED REV. DESCRIPTION DATE 1.2 FOR PATENT INFO: https://www.adwpat.com MSM 2.0 DESIGN NOTES **INITIAL RELEASE** ΤP 21NOV11 2.2 FITS MONOPOLES 10"-50" O.D. 2.1 MT38248 USED FOR MONOPOLES 30"-50" O.D. MSM В UPDATE MTC328601 ΤP 3.0 MANUFACTURING/SPECIAL REQUIREMENTS 05SEP12 3.1 TIGHTEN ALL BOLTS SECURING FLAT PLATES BY THE TURN-OF-NUT METHOD. TIGHTEN ALL RJC U-BOLTS USING TURN-OF-NUT METHOD WITH ATTENTION TO LEAVE EQUAL DISTANCE AND С REDESIGN AND UPDATED DWG 8000029994 30MAY18 EQUAL FORCE ON EACH LEG OF THE U-BOLT. $D|_{4.0}$ TEST RJC D THREADED ROD & HDW WAS 1/2" 8000033466 22JAN19 5.0 PACKAGING 5.1 PACKAGING SHALL MEET ANDREW REQUIREMENTS PER DOCUMENT IS-PL-3005
5.2 PRINTED DOCUMENT TO BE PLACED INSIDE POLYBAG AND THEN IN SHIPPING CONTAINER YC1059 BA1025 Ε UPDATED DRAWING FORMAT 16OCT25 50105402AMO 5.3 EXTRA HARDWARE MAY BE SUPPLIED, BAGGED AND SHIPPED 50 [1270.0] Ø 10 254.0 (6.5[165.1])**ANDREW**® an Amphenol company SAP MATERIAL MASTER 0 PLACE $X[.X] \pm 0.25[6.3]$ $2 \text{ PLACE} \quad .XX[.X] \pm 0.060[1.5]$ MC-RR1050-3 1 PLACE $.X[.X] \pm 0.12[3.0]$ ANGLES ± 2° MATERIAL **FINISH** COMPONENT PART NUMBERS PROVIDED FOR ASSEMBLY PURPOSES: DATE TITLE INDIVIDUAL COMPONENTS MAY BE SHIPPED AS PARTS WITHIN AN INCLUDED KIT. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES INTERPRET PER ANSI Y 14.5M-1 CE RJC 22JAN19 10" - 50" RRU MONOPOLE MOUNT Α 10/16/2025 ITEM PART NO. RW YC1059 DESCRIPTION WEIGHT NOTE NO. DENSITY 1 MTC328602 WELDMENT, LIGHT DUTY 10-50 RINGMOUNT 3 26.39 LBS MASS | 157.20 AD YMENG 10/20/2025 4.15 LBS 2 MT38248 5/8" X 48" GALV THREADED ROD 6 2.2 SCALE DOCUMENT NO. VOLUME 556.66 RE YMENG 10/21/2025 MC-RR1050-3 1:8 GUB-4240 0.56 LBS 3 1/2" X 2-1/2" X 4" GALV U-BOLT 6 SURFACE AREA 6186.28 ECN 50105402AMO GWL-05 0.03 LBS 4 5/8" GALV LOCK WASHER 12 HEIGHT 6.5" SIZE Auth Group INSL MODEL **DRAWING** SHEET 5 GN-05 5/8" GALV HEX NUT 12 0.08 LBS LENGTH 43.0" VERSION STATUS REVISION VERSION STATUS REVISION Confidential 1 OF 1 MT-382-24 5/8" X 24" GALV THREADED ROD 6 2.07 LBS WIDTH 43.0" RE RE F 01

2