

PE-6RRU-16



HELIAX® Break Out Power Box for 6 RRU/AAU 1 Power Trunk, 6 Power Jumpers, Grey Terminal Blocks, 2 Grounding blocks

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Europe Latin America North America
Product Type	Outdoor junction box
Product Brand	HELIAX®

General Specifications

Application	Used as a fiber/power junction box
Cable Entry Location	Bottom
Cable Entry, quantity, maximum, bottom	1
Color	Gray
Mounting	Pole Wall

Dimensions

Height	317.5 mm 12.5 in
Width	266.7 mm 10.5 in
Depth	152.4 mm 6 in
Jumper Breakout Length, Maximum	150 mm 5.906 in
Jumper Outlet, Quantity, Maximum	6
Jumper Outlet Diameter, Minimum	9 mm 0.354 in
Jumper Outlet Diameter, Maximum	16 mm 0.63 in
Trunk Entry, Diameter, Minimum	21 mm 0.827 in
Trunk Entry, Diameter, Maximum	32 mm 1.26 in
Trunk Entry, Quantity, Maximum	1

Material Specifications

Material Type	High-impact polycarbonate, UV resistant
----------------------	---

PE-6RRU-16

Environmental Specifications

Operating Temperature	-40 °C to +75 °C (-40 °F to +167 °F)
Environmental Space	Indoor Outdoor
Qualification Standards	IEC 60529, IP65

Packaging and Weights

Included	Mounting kit
Weight, net	2.268 kg 5 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

