

V17-010-01-A0-E



2-port Venue Antenna, 1695-2690 MHz, 17° HPBW, Fixed Tilt

- Designed with CleanBeam™ technology
- 2T2R MetaLens™ antenna
- Supports 2x2 MIMO
- 17° azimuth and 17° elevation beamwidth

General Specifications

Color	White
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Radome Material	ASA, UV resistant
RF Connector Interface	4.3-10 Female
RF Connector Quantity, total	2

Dimensions

Width	503 mm 19.803 in
Depth	684 mm 26.929 in
Length	503 mm 19.803 in
Net Weight, without mounting kit	14 kg 30.865 lb

Port Configuration

V17-010-01-A0-E



Electrical Specifications

Operating Frequency Band	1695 – 2690 MHz
Polarization	±45°

Electrical Specifications

	Y1,Y2	Y1,Y2	Y1,Y2	Y1,Y2
Frequency Band, MHz	1695–1890	1850–1990	1990–2200	2200–2690
RF Port	1,2	1,2	1,2	1,2
Gain, dBi	18	18.5	18.9	20
Beamwidth, Horizontal, degrees	21	20	19	16
Beamwidth, Vertical, degrees	21	20	19	16
USLS (First Lobe), dB	20	21	21	22
Front-to-Back Ratio at 180°, dB	38	40	40	42
Front-to-Back Ratio, Copolarization 180° ± 30°, dB	33	36	34	30
Isolation, Cross Polarization, dB	25	25	25	25
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153
Input Power per Port, maximum, watts	200	200	200	200

Packaging and Weights

V17-010-01-A0-E

Width, packed	616 mm 24.252 in
Depth, packed	750 mm 29.528 in
Length, packed	826 mm 32.52 in
Weight, gross	27 kg 59.525 lb

Regulatory Compliance/Certifications

Agency	Classification
UK-ROHS	Compliant

Included Products

- 600899A-2 - Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

600899A-2



Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

Product Classification

Product Type Downtilt mounting kit

General Specifications

Application Outdoor

Color Silver

Dimensions

Compatible Diameter, maximum 114.3 mm | 4.5 in

Compatible Diameter, minimum 61 mm | 2.402 in

Weight, net 3.9 kg | 8.598 lb

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 1

Weight, gross 4.2 kg | 9.259 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

600899A-2

