

NNH4-45B-HG-R3B



12-port Next Generation PerforMax™ Superior Coverage and Capacity sector antenna, 4x 698-896 and 8x 1695–2200 MHz, 45° HPBW, 6 ft, 3x RET

- Antenna optimized for higher gain with superior radiation efficiency
- Powered by Andrew's SEED® technology (Sustainable Energy Efficient Design)
- Narrow beamwidth capacity antenna for higher level of densification and enhanced data throughput
- Best in class PIM immunity
- Superior patterns for enhanced interference mitigation resulting in improved SINR, higher throughput, and more capacity
- Internal SBT allows remote RET control from the radio over the RF jumper cable

General Specifications

Antenna Type	Sector
Band	Multiband
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, mid band	8
RF Connector Quantity, low band	4
RF Connector Quantity, total	12


Remote Electrical Tilt (RET) Information

RET Hardware	CommRET v2
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	3 female 3 male
Input Voltage	10–30 Vdc
Internal Bias Tee	Port 1 Port 5 Port 9
Internal RET	Low band (1) Mid band (2)
Power Consumption, active state, maximum	10 W
Power Consumption, idle state, maximum	2 W

NNH4-45B-HG-R3B

Protocol	3GPP/AISG 2.0
Dimensions	
Width	749 mm 29.488 in
Depth	197 mm 7.756 in
Length	1848 mm 72.756 in
Net Weight, without mounting kit	56 kg 123.459 lb

Array Layout



Array ID	Frequency (MHz)	RF Connector	HPBW	RET (dB)	AISG No.	RET UID
R1	698-896	1 - 2	45°	1	AISG1	CPxxxxxxxxxxxxxxxxR1
R2	698-896	3 - 4	45°			
R3	1695-2200	5 - 6	45°	2	AISG2	CPxxxxxxxxxxxxxxxxR3
R4	1695-2200	7 - 8	45°			
R5	1695-2200	9 - 10	45°	3	AISG3	CPxxxxxxxxxxxxxxxxR5
R6	1695-2200	11 - 12	45°			

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration



Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1695 – 2200 MHz 698 – 896 MHz

NNH4-45B-HG-R3B

Polarization	±45°
Total Input Power, maximum	1,440 W

Electrical Specifications

	R1,R2	R1,R2	B1-B4	B1-B4	B1-B4
Frequency Band, MHz	698–806	806–896	1695–1880	1850–1990	1920–2200
RF Port	1-4	1-4	5-12	5-12	5-12
Gain, Maximum, dBi	16.9	17.5	20.1	20.6	20.9
Gain, dBi	16.2	16.9	19.1	19.7	20.1
Beamwidth, Horizontal, degrees	49	45	49	47	45
Beamwidth, Vertical, degrees	12.4	11.1	5.3	5	4.7
Beam Tilt, degrees	2–12	2–12	0–10	0–10	0–10
USLS (First Lobe), dB	18	17	15	16	17
Front-to-Back Ratio, Copolarization 180° ± 30°, dB	27	31	32	36	35
CPR at Boresight, dB	15	14	16	20	18
Isolation, Cross Polarization, dB	25	25	25	25	25
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153	-153
Input Power per Port at 50°C, maximum, watts	300	300	250	250	250

Mechanical Specifications

Wind Loading @ Velocity, frontal	1,768.0 N @ 150 km/h (397.5 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	191.0 N @ 150 km/h (42.9 lbf @ 150 km/h)
Wind Loading @ Velocity, maximum	1,768.0 N @ 150 km/h (397.5 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	1,768.0 N @ 150 km/h (397.5 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	915 mm 36.024 in
Depth, packed	357 mm 14.055 in
Length, packed	2438 mm 95.984 in
Weight, gross	80 kg 176.37 lb

NNH4-45B-HG-R3B

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Included Products

BSAMNT-9	–	Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.
----------	---	--

* Footnotes

Performance Note	Severe environmental conditions may degrade optimum performance
------------------	---

BSAMNT-9



Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

Product Classification

Product Type Downtilt mounting kit

General Specifications

Application Outdoor

Color Silver

Dimensions

Compatible Diameter, maximum 115 mm | 4.528 in

Compatible Diameter, minimum 60 mm | 2.362 in

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 1

Weight, gross 9.7 kg | 21.385 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



