

FT-02LENDN



HELIAX® Discrete single mode 2 fiber cable, HHC Plug to HHC Jack, OptiTip Compatible connector

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Wireless Fiber Cable Assemblies
Product Brand	HELIAX®
Product Series	FT
Ordering Note	ANDREW® non-standard product

General Specifications

Construction Type	Discrete fiber tail
Interface, Connector A	HHC (HELIAX® Hardened Connector) OptiTip & HMFOC Compatible
Interface Body Style, connector A	Straight
Interface, Connector B	HHC (HELIAX® Hardened Connector) OptiTip & HMFOC Compatible
Interface Feature, connector B	Outdoor
Interface Body Style, connector B	Straight
Jacket Color	Black
Total Fibers, quantity	2

Dimensions

Cable Assembly Length Range (m)	5 – 30
Diameter Over Jacket	5.4 mm 0.213 in

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	G.657.A2
Insertion Loss, typical note	Insertion loss is measured at 1310 and 1550 nm
Insertion Loss, typical	0.75

FT-02LENDN

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space	Outdoor

Packaging and Weights

Cable weight	19 kg/km 12.767 lb/kft
---------------------	--------------------------

* Footnotes

Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)