

L8B1-D8-A00D00-00 | CMC8L



Empty CMC8L 300W HVAC w/ 300W Heater Heater Outdoor Battery Cabinet

The cabinet is designed to house rack mounted equipment and a battery string. This includes DC power systems, Fiber storage/splice trays, cell site routers, batteries, and other rack mounted equipment. This cabinet provides mechanical and environmental protection for the equipment inside.

- Excellent Thermal Performance compatible with a DAC or HVAC
- Provides mounting space for power distribution, network servers, batteries, or other equipment.
- Front door compatible with Pad Lock.
- Provides flexible access for the cable entrances.
- Optional heater for cold environments.
- Provides 8RU of 19" or 23" Rack Space for Equipment
- Common parts available across the same platform.

Product Classification

Product Type	Outdoor cabinet
Product Series	CMC

General Specifications

Access	Front door Removable panel
Alarm Type	Door alarm HVAC alarms (including high temperature, failure) S2 module, 20P or standard and user defined alarms
Batteries	Not included
Battery Storage	1 shelf
Cabinet Type	Battery cabinet
Capacity	500W Heater
Color	Gray
Cooling	300W HVAC w/ 300W Heater
Cooling Type	Direct air cooling
Door Security	Quarter turn lock, puck lock system for rear door Swing handle, puck lock system for front door
Equipment Storage	No equipment storage available

L8B1-D8-A00D00-00 | CMC8L

Mounting	H-frame Pad Pole Universal wall mount
Noise Emission, maximum	65 dBA
Rack Type	EIA 19 in EIA 23 in
Rack Units	8

Dimensions

Height	558.8 mm 22 in
Width	711.2 mm 28 in
Depth	711.2 mm 28 in

Electrical Specifications

Battery String Current, maximum	100 A-h @ -48 Vdc
Battery Strings, quantity	1 @ -48 Vdc
Cooling Capacity	600 W
dc Distribution Type	19" or 23" Rack DC Distribution Panels or DIN Breakers

Material Specifications

Finish	Powder coated UV resistant
Material Type	Aluminum

Environmental Specifications

Operating Temperature	-40 °C to +46 °C (-40 °F to +115 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space	UV resistant for outdoor
Qualification Standards	IP55 Telcordia GR-487
Thermal Compliance	GR-487

Packaging and Weights

Weight, net	40.823 kg 90 lb
-------------	-------------------

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system