
F1CLAMP-CNL-E2B



KwikClamp™ Hanger for 1/4" cable, double stack, C-Channel compatible; includes hardware

Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa | Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger	2
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	Channel section 40 x 22 x 1.5 mm

Dimensions

Height	138 mm | 5.433 in
Width	22 mm | 0.866 in
Length	42 mm | 1.654 in
Compatible Diameter, maximum	7.5 mm | 0.295 in
Compatible Diameter, minimum	6.5 mm | 0.256 in
Nominal Size	1/4 in
Hanger Spacing, maximum	1.83 m | 6.004 ft

Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

Material Specifications

Material Type	Engineered plastic | Stainless steel

Mechanical Specifications

©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: November 4, 2026

ANDREW® an Amphenol company

Vibration Survival	≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Corrosion Resistance, minimum with no degredation	≥500 hours in salt spray chamber
Environmental Strength Capability	Five times cable weight
UV Resistance, minimum with no degradation	≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed	27 cm | 10.63 in
Width, packed	21 cm | 8.268 in
Length, packed	11 cm | 4.331 in
Included	Hardware
Packaging quantity	100
Weight, gross	4.89 kg | 10.781 lb

©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: November 4, 2026