



## MR2618 Indoor Coverage and High Speed Data Enhancer for 2600 MHz LTE Applications

### Product Classification

**Product Type** RF repeater unit

### General Specifications

**Antenna Interface at Repeater** SMA Female  
**Indoor Antenna** Optional, not included  
**Optional Antenna Gain** 2 dBi  
**Optional Antenna Type** Omni  
**Performance Note** Values typical, unless otherwise stated  
**Supervision/Control Option** Heartbeat via SMS | Remote control

### Dimensions

**Height** 240 mm | 9.449 in  
**Width** 240 mm | 9.449 in  
**Depth** 35 mm | 1.378 in  
**Optional Antenna Length** 107 mm | 4.213 in

### Electrical Specifications

**Gain, typical** 75 dB  
**Gain Adjustment Range** 30 dB  
**License Band** LTE 2600  
**Local Power** 6 Vdc  
**Mains Power** 100–240 Vac  
**Return Loss** 10 dB  
**Power Consumption** 27 W

## Electrical Specifications, Rx (Uplink)

<b>Operating Frequency Band</b>	2500 – 2570 MHz
<b>Output Power @ One Carrier</b>	18 dBm
<b>Output Power @ Two Carriers</b>	15 dBm
<b>Output Power Note</b>	Possible slight degradation of LTE requirement unwanted emission limit at certain passband adjustments and carrier constellation

## Electrical Specifications, Tx (Downlink)

<b>Operating Frequency Band</b>	2620 – 2690 MHz
<b>Output Power @ One Carrier</b>	18 dBm
<b>Output Power @ Two Carriers</b>	15 dBm

## Environmental Specifications

<b>Operating Temperature</b>	+5 °C to +40 °C (+41 °F to +104 °F)
<b>Ingress Protection Test Method</b>	IEC 60529:2001, IP30

## Packaging and Weights

<b>Weight, net</b>	1.5 kg   3.307 lb
--------------------	-------------------

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

