ATCB-DB9-016



RET control cable 16m with male DB9 and female AISG connector

- Feeds data and power to RET system components
- Directly connects RET actuator with RRH (Remote Radio Heads) with DB9 connector

OBSOLETE

This product was discontinued on: May 31, 2016

Replaced By:

ATCB-DB9-020 RET control cable 20m with male DB9 and female AISG connector

Product Classification

Product Type AISG DB9 cable

General Specifications

AISG Connector A 8-pin DIN Female

AISG Connector A Body Style Straight

AISG Connector A Standard IEC 60130-9

Color Black

Connector B 9-pin D-sub Male

Data Conductor Type 0.24 mm² (24 AWG) twisted pair

EU Certification CB | CE

Power Conductor Type 0.82 mm² (18 AWG) stranded

Dimensions

 Length
 16 m | 52.493 ft

 Diameter Over Jacket
 8 mm | 0.315 in

Electrical Specifications

Protocol AISG 1.1 | AISG 2.0

Voltage, maximum 300 V

Environmental Specifications



ATCB-DB9-016

Operating Temperature $-40 \,^{\circ}\text{C} \text{ to } +70 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +158 \,^{\circ}\text{F})$

Relative Humidity Up to 100%

Climatic Sequence Test Method IEC 60068-2-14

Corrosion Test Method IEC 60068-2-11, Test Condition Ka

Ingress Protection Test Method IEC 60529:2001, IP67

UV Resistance Test Method IEC 60068-2-5, Test Condition B

Packaging and Weights

Weight, net 1.8 kg | 3.968 lb

Regulatory Compliance/Certifications

Agency Classification
AISG Compliant

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

AISGY | LILI