


# L4A-PDMDM-VA

---

Base Product



## Product Classification

|                       |                                      |
|-----------------------|--------------------------------------|
| <b>Product Type</b>   | Wireless transmission cable assembly |
| <b>Product Series</b> | LDF4-50A                             |

## General Specifications

|   |  |
|---|--|
| <b>Body Style, Connector A</b>            | Straight   |
| <b>Body Style, Connector B</b>            | Straight   |
| <b>Interface, Connector A</b>             | 7-16 DIN Male  |
| <b>Interface, Connector B</b>             | 7-16 DIN Male  |
| <b>Specification Sheet Revision Level</b> | A  |
| <b>Variable Length</b>                    | For custom lengths, contact your local ANDREW representative |

## Dimensions

|                     |            |
|---------------------|------------|
| <b>Length</b>       | 0 m   0 ft |
| <b>Nominal Size</b> | 1/2 in     |

## Electrical Specifications

|                         |        |
|-------------------------|--------|
| <b>DTF, Connector A</b> | -32 dB |
| <b>DTF, Connector B</b> | -32 dB |

## VSWR/Return Loss

| Frequency Band | VSWR | Return Loss (dB) |
|----------------|------|------------------|
| 806–960 MHz    | 1.11 | 26.4             |
| 1700–2170 MHz  | 1.11 | 26.4             |

## Jumper Assembly Sample Label

# L4A-PDMDM-VA

---



## Environmental Specifications

### Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition