

# F4C-HMHM-P

Base Product



HELIAX® 1/2" Superflexible SureFlex® Jumper with interface types 4.3-10 Male and 4.3-10 Male

## General Specifications

|                         |                  |
|-------------------------|------------------|
| Attachment, Connector A | Factory attached |
| Attachment, Connector B | Factory attached |
| Body Style, Connector A | Straight         |
| Body Style, Connector B | Straight         |
| Interface, Connector A  | 4.3-10 Male      |
| Interface, Connector B  | 4.3-10 Male      |

## Electrical Specifications

|                                  |                      |
|----------------------------------|----------------------|
| 3rd Order IMD Static             | -119 dBm             |
| 3rd Order IMD Static Test Method | Two +43 dBm carriers |
| DTF, Connector A                 | 34 dB                |
| DTF, Connector B                 | 34 dB                |

## VSWR/Return Loss

| Frequency Band | VSWR  | Return Loss (dB) |
|----------------|-------|------------------|
| 698–970 MHz    | 1.065 | 30               |
| 1700–2200 MHz  | 1.065 | 30               |
| 2200–2700 MHz  | 1.083 | 28               |
| 3400–3800 MHz  | 1.222 | 20               |

## Regulatory Compliance/Certifications

| Agency        | Classification                                                                 |
|---------------|--------------------------------------------------------------------------------|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |