

F4C-NMNM-P-SGW

Base Product



HELIAX® 1/2" Superflexible SureFlex® Jumper with interface types N Male and N Male with HELIAX® SureGuard weatherproofing

Product Classification

Product Type	SureFlex® Premium, static PIM
Product Brand	HELIAX® SureFlex® SureGuard®
Product Series	RSJ4-50

General Specifications

Attachment, Connector A	Factory attached
Attachment, Connector B	Factory attached
Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	N Male
Interface, Connector B	N Male
Variable Length	For custom lengths, contact your local ANDREW representative

Dimensions

Nominal Size	1/2 in
--------------	--------

Electrical Specifications

3rd Order IMD Static	-112 dBm
3rd Order IMD Static Test Method	Two +43 dBm carriers
DTF, Connector A	34 dB
DTF, Connector B	34 dB

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.065	30
1700–2200 MHz	1.065	30
2200–2700 MHz	1.106	26

F4C-NMNM-P-SGW

Environmental Specifications

Immersion Test Method IEC 60529:2001, IP68

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system