

F4C-HPHMDR

Base Product



HELIAX® 1/2" Superflexible SureFlex® Jumper with interface types 4.3-10 DIN Male and 7-16 DIN Male, right angle

Product Classification

Product Type	SureFlex® HP, HELIAX® performance
Product Brand	HELIAX® SureFlex®
Product Series	RSJ4-50

General Specifications

Attachment, Connector A	Factory attached
Attachment, Connector B	Factory attached
Body Style, Connector A	Straight
Body Style, Connector B	Right angle
Interface, Connector A	4.3-10 Male
Interface, Connector B	7-16 DIN Male
Variable Length	For custom lengths, contact your local ANDREW representative

Dimensions

Nominal Size	1/2 in
--------------	--------

Electrical Specifications

3rd Order IMD Static Test Method	Two +43 dBm carriers
3rd Order IMD, typical	-116 dBm
DTF, Connector A	34 dB
DTF, Connector B	32 dB

VSWR/Return Loss

Frequency Band	VSWR, typical	Return Loss, typical (dB)
698–970 MHz	1.083	28
1700–2200 MHz	1.083	28
2200–2700 MHz	1.135	24

F4C-HPHMDR

3400–3800 MHz	1.222	20
---------------	-------	----

Environmental Specifications

Immersion Test Method	IEC 60529:2001, IP68
-----------------------	----------------------

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system